

## invisible loudspeakers Technical Specifications

## Base

English word, referring to the Base of Music as in Bass! Can be installed into a Baseboard or Kickplate of cabinets



Model: Base

Application: Hidden with Slim Port into Space

Port Finish: Port via Baseboard or Cabinet Kick plate

Frequency Response: 29Hz -170Hz (+/- 3db)

Dimensions: H 265mm x W 255mm x D 89mm

H 14.3" x W 10" x D 3.5"

plus mounting plate Fits between studs and 2x4s

Cut out size: 4 x Slim 1/4" slots by 9-1/2"

Part of Plate provided

Driver: 3"x10" Carbon Fibre High performance Driver

with Dual VC Neodymium Magnet

Impedance: Nominal 6 ohms

Power Handling: 150 W RMS (Peak 300W)

Sensitivity: 2,83V/1M 89DB

Operating Temperature: -15 degrees Celsius to 50 degrees Celsius Connection Type: Phoenix Connector, accepts 24-12 AWG Isolated Plate to connect enclosure to

structure. With Side firing port

(opt. Horiz. vent for kick plate/under furniture) Fully Welded Aluminum and Rubber isolation

Construction: Fully Welded Aluminum and Ru

Manufactured: Made in Canada

Warranty: 5 Year Replacement warranty