

Mooi

Dutch word, similar to the word 'Nice'
Definition: beautiful, elegant, clean



Model:	Mooi
Frequency Response:	75Hz ~ 20KHz (+/- 3dB)
Dispersion Angle:	180 degrees x 180 degrees (H x V) Full Spectrum within 2dB
Dimensions:	581 mm x 245 mm x 79 mm (H x W x D) 23" x 9-3/4" x 3-1/2"
Cut out size:	Width x Height 9-3/4" x 16-5/8"
Weight:	4350 g
Impedance:	Nominal 8 ohms (minimum 8 ohms)
Power Handling:	80 W Maximum (overload protection built-in)
Sensitivity:	86 dB @ 1 m/ 1W (with 2 mm plaster skim)
Maximum SPL:	105 dB @ 1 m/ 80W (with 2 mm plaster skim)
Operating Temperature:	-15 degrees Celsius to 50 degrees Celsius
Connection Type:	Phoenix, screw in, accepts 24-12 AWG
Filtering and Protection:	Overload protection and HPF built-in
Hardware provided:	All required for installation in 3/8" to 1" thick drywall board (optional install handle)
Construction:	Aluminum honeycomb core, doped paper skin, composite acoustic panel. Acoustically tuned aluminum enclosure
Manufacturer:	Nakymatone, Made in Canada Patent Pending